



G.726 Codec

Product Data Sheet

V 1.1

Date: April 1, 2010

Features

- Fully bit exact with ITU-T G.726
- Supports A-law, μ -law or 16bit linear PCM input for encoding
- Supports A-law and μ -law or 16bit linear PCM output for decoding
- Supports both sample-by-sample and block based processing
- Sampling frequency 8 kHz
- 16, 24, 32 or 40 Kbps bit stream rate
- Variable frame/buffer memory size according to the system needs
- Simple application interface

Supported Platforms

- Hardware – i.MX ARM platforms
- Software – eLinux, Windows® Embedded CE operating systems

Performance Outline

i.MX ARM9™ eLinux

Typical spec: 8KHz, 64kbps for encoder
8KHz, 128kbps for decoder

Performance (MHz): 7.48 for encoder
8.30 for decoder

Memory Footprint(KB)

- ROM: 16.5
- RAM: 0.4

i.MX ARM9™ WinCE

Typical spec: 8KHz, 64kbps for encoder
8KHz, 128kbps for decoder

Performance (MHz): 8.31 for encoder
9.49 for decoder

Memory Footprint(KB)

- ROM: 16.5
- RAM: 0.4

i.MX ARM11 eLinux

Typical spec: 8KHz, 64kbps for encoder
8KHz, 128kbps for decoder

Performance (MHz): 6.59 for encoder
7.24 for decoder

Memory Foot Print(KB)

- ROM: 16.5
- RAM: 0.4

i.MX ARM11 WinCE

Typical spec: 8KHz, 64kbps for encoder
8KHz, 128kbps for decoder

Performance (MHz): 7.09 for encoder
7.85 for decoder

Memory Foot Print(KB)

- ROM: 16.5
- RAM: 0.4

Performance measurements can deviate based on ARM core, memory and cache configuration on the board.
To measure directly, enable the TIME_PROFILE in the test application provided in the release package.

For further details, contact Freescale customer representative.

Copyright © 2007, 2010 Freescale Semiconductor. All rights reserved.

Freescale Confidential Proprietary